Special lighting fixtures for outdoor parking lots, tunnels, bus stops, square lighting, etc.

IP67	10 / 5 kg / 40 cm / 20 J	ABOVE WATER	PENDANT MOUNTED	Class III	CE	RoHS	RECYCLABLE
IP Rating	IK Rating	Water Depth	Mounting Method	Safety Class	Certification Mark	Environmental Mark	Recyclable Mark

DIMENSIONS



unit: mm

TECHNICAL DATA

L19C

ELECTRICAL	**ELECTRICAL PARAMETERS**	
	Typical Power | Power Consumption	20W / 40 W / 60 W
	Input | Current	AC90~265
	Control Method | Control	ON OFF/ DALI
	Cable Order | Wiring	1 in (one in)
	Security Level | Class	Class III
LIGHT SOURCE	**LED LIGHT SOURCE PARAMETERS**	
	LED Chip Brand | Brand	Osram
	LED Chip Type | Type	3030
	LED Quantity | Qty	60 PCS/120 PCS/180 PCS
	Colour (CCT) | Colour	2200K/2700K/3000K/4000K/6500K
	CRI | Rendering	Ra ≥ 70/Ra ≥ 80/Ra ≥ 90
	Typical Light Efficiency | Efficacy	>100 lm/W (3000K) · >110 lm/W (4000K) · >120 lm/W (6500K)
	Lifetime | Life	50,000 H
STRUCTURE	**STRUCTURAL PARAMETERS**	
	Material | Housing	Aluminum
	Cover | Glass	PMMA, T = 3 mm
	Beam Angle | Angle	98°
	Product Dimensions | Size	See DIMENSIONS drawing
	Weight | Mass	1.3 kg@1M
ENVIRONMENT	**ENVIRONMENTAL PARAMETERS**	
	Working Temperature | Temp	-25°C ~ +45°C
	Storage Humidity | Humidity	0 ~ 90%
	IP Code | IP	IP67
	IK Code | IK	IK10

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

Beam 98°



SYSTEM DIAGRAM

WIRING TOPOLOGY

ON/OFF



DALI



WIRE COLOUR DEFINITION

L19C

WIRING COLOUR / DESIGNATION REFERENCE

Non-Dimmable Line Voltage 220 to 240 Vac - International

DESIGNATION	COLOR
Line	Brown
Neutral	Blue
Ground/Earth	Green/ Yellow



WIRING COLOUR / DESIGNATION REFERENCE

Non-Dimmable Line Voltage 120/277 Vac - North America

DESIGNATION	COLOR
Line	Black
Neutral	White
Ground/Earth	Green



WIRING COLOUR / DESIGNATION REFERENCE

DALI Line Voltage 220 to 240 Vac - International

DESIGNATION	COLOR
Line	Brown
Neutral	Blue
Ground/Earth	Green/ Yellow
DALI+	Grey
DALI-	Black



WIRING COLOUR / DESIGNATION REFERENCE

DALI Line Voltage 120/277 Vac - North America

DESIGNATION	COLOR
Line	Black
Neutral	White
Ground/Earth	Green
DALI+	Purple
DALI-	Pink or Grey



INSTALLATION & USAGE NOTES

PRECAUTIONS

OBSERVE THE FOLLOWING PRECAUTIONS WHEN INSTALLING AND OPERATING THE LUMINAIRE

- Installation and wiring must be carried out by a qualified electrician in accordance with local electrical codes and these instructions.
- Operate the luminaire only on the rated low-voltage DC supply (see Technical Parameters); never connect it directly to mains voltage.
- Do not energise the luminaire out of water for extended periods — dry operation may cause overheating and shorten LED life.
- Inspect cables, seals and glands periodically; damaged sheaths or ageing seals must be replaced immediately by qualified personnel.
- Always isolate the power supply before installation, maintenance or lamp replacement; verify the circuit is de-energised before touching any connector.
- All cable entries, glands and junction boxes must be properly sealed to keep the IP68 rating; use only the supplied or approved waterproof connectors.
- Maintain pool / water-feature water chemistry (pH and chlorine levels) within normal ranges to preserve the SUS316 stainless-steel housing and trims.
- Use only genuine LESAN replacement parts; any unauthorised modification voids the warranty.