
XT011



Special lighting fixtures for buildings, tunnels, bridges, gardens, squares, etc.

IP65	08 5 kg 10 cm 5 J	ABOVE WATER	SURFACE MOUNTED	Class III	CE	RoHS	RECYCLABLE
IP Rating	IK Rating	Water Depth	Mounting Method	Safety Class	Certification Mark	Environmental Mark	Recyclable Mark

DIMENSIONS



unit: mm

TECHNICAL DATA


XT011

ELECTRICAL	**ELECTRICAL PARAMETERS**	
	Typical Power | Power Consumption	36 W / 48 W
	Input | Current	AC90~265V
	Control Method | Control	ON OFF/DMX512 / DALI / 0-10V
	Cable Order | Wiring	1 in 1 out
	Security Level | Class	Class III
LIGHT SOURCE	**LED LIGHT SOURCE PARAMETERS**	
	LED Chip Brand | Brand	CREE/lumileds
	LED Chip Type | Type	RJ5050 / TX3535
	LED Quantity | Qty	24 PCS
	Colour (CCT) | Colour	2200K/2700K/3000K/4000K/6500K/RGBW
	CRI | Rendering	Ra ≥ 70/Ra ≥ 80/Ra ≥ 90
	Typical Light Efficiency | Efficacy	>80 lm/W (3000K) · >30 lm/W (RGBW)
	Lifetime | Life	50,000 H
STRUCTURE	**STRUCTURAL PARAMETERS**	
	Material | Housing	Aluminum
	Cover | Glass	Super-transparency tempered glass, T = 4 mm
	Beam Angle | Angle	10°/30°/60°/20*45°
	Product Dimensions | Size	See DIMENSIONS drawing
	Weight | Mass	2.47 kg@1M
ENVIRONMENT	**ENVIRONMENTAL PARAMETERS**	
	Working Temperature | Temp	-25°C ~ +45°C
	Storage Humidity | Humidity	0 ~ 90%
	IP Code | IP	IP65
	IK Code | IK	IK08


LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

Beam 10° / 22°×42° / 30° / 60°


BEAM ANGLE 10°




BEAM ANGLE 22°×42°



BEAM ANGLE 30°



BEAM ANGLE 60°




SYSTEM DIAGRAM

WIRING TOPOLOGY


ON/OFF



built-in DMX



DALI 0-10V




WIRE COLOUR DEFINITION

XT011

WIRING COLOUR / DESIGNATION REFERENCE

Non-Dimmable Line Voltage 220 to 240 Vac - International


DESIGNATION	COLOR
Line	Brown
Neutral	Blue
Ground/Earth	Green/ Yellow



WIRING COLOUR / DESIGNATION REFERENCE

Non-Dimmable Line Voltage 120/277 Vac - North America


DESIGNATION	COLOR
Line	Black
Neutral	White
Ground/Earth	Green



WIRING COLOUR / DESIGNATION REFERENCE

DALI Line Voltage 220 to 240 Vac - International


DESIGNATION	COLOR
Line	Brown
Neutral	Blue
Ground/Earth	Green/ Yellow
DALI+	Grey
DALI-	Black



WIRING COLOUR / DESIGNATION REFERENCE

0-10 V Line Voltage 220 to 240 Vac - International

DESIGNATION	COLOR
Line	Brown
Neutral	Blue
Ground/Earth	Green/ Yellow
0-10V+	Grey
0-10V-	Black



INSTALLATION & USAGE NOTES

PRECAUTIONS

OBSERVE THE FOLLOWING PRECAUTIONS WHEN INSTALLING AND OPERATING THE LUMINAIRE

- Installation and wiring must be carried out by a qualified electrician in accordance with local electrical codes and these instructions.
- Operate the luminaire only on the rated low-voltage DC supply (see Technical Parameters); never connect it directly to mains voltage.
- Do not energise the luminaire out of water for extended periods — dry operation may cause overheating and shorten LED life.
- Inspect cables, seals and glands periodically; damaged sheaths or ageing seals must be replaced immediately by qualified personnel.
- Always isolate the power supply before installation, maintenance or lamp replacement; verify the circuit is de-energised before touching any connector.
- All cable entries, glands and junction boxes must be properly sealed to keep the IP68 rating; use only the supplied or approved waterproof connectors.
- Maintain pool / water-feature water chemistry (pH and chlorine levels) within normal ranges to preserve the SUS316 stainless-steel housing and trims.
- Use only genuine LESAN replacement parts; any unauthorised modification voids the warranty.